## **CHV-RTHS**

## Remote Temperature and Humidity Sensor



- Wall-mounted remote temperature and humidity sensor
- Designed for use with select Crestron® thermostats
- Can be mounted up to 500 ft (152 m) from the thermostat
- Optional MMK-RS pre-construction mounting kit (sold separately) allows for simplified rough-in for wiring and positioning, as well as an option to completely flush mount the sensor.

The <u>CHV-RTHS</u> is a wall-mounted remote temperature and relative humidity sensor designed for use with select Crestron® thermostats. Using CAT5 or similar low-capacitance wire, the remote sensor can be mounted up to 500 ft (152 m) from the thermostat. One-piece mounting and a single nonpolarized twisted-pair connection make the CHV-RTHS simple to install. The 1-1/2 in. diameter face protrudes just 1/8 in. from the wall surface and is easily painted or wallpapered to blend into the wall surface.

Use with the MMK-RS (sold separately) to simplify the wiring and sensor positioning during the rough-in stage of construction. The MMK-RS has an option to completely flush mount the sensor and make it virtually hidden on a wall.

### **Specifications**

#### Measurement Range

Indoor 0° to 110°F (-18° to 43°C)

Temperature

Outdoor -30° to 120°F (-35° to 49°C)

Temperature

Humidity 0% to 100% RH

#### **Temperature Tolerance**

Over Full Range  $\pm 1^{\circ}F (\pm 0.5^{\circ}C)$ At Room  $\pm 1^{\circ}F (+0.1/-0.4^{\circ}C)$ 

**Temperatures** 

### **Humidity Tolerance**

+5%

#### Connections

(1) 10 in. (254 mm) 2-wire twisted-pair pigtail, 22 AWG; Nonpolarized connection to remote sensor input on the thermostat;

Maximum Cable Length: 500 ft (152 m) via CAT5

#### Construction

Material Cylindrical plastic;

Primed metal cap suitable for paint or

wallpaper

**Mounting** Drywall mountable in a 1 in. (26 mm)

diameter round hole, protrudes ~1/8 in.

(3 mm) from wall surface;

Flush drywall mount or non-drywall surface mount with  $\overline{\text{MMK-RS}}$  mounting kit (sold

separately)

Dimensions

 Diameter
 1.50 in. (39 mm)

 Depth
 2.22 in. (57 mm)

#### Model

#### **CHV-RTHS**

Remote Temperature and Humidity Sensor

#### **Available Accessories**

For a list of available accessories, visit the  $\underline{\text{CHV-RTHS}}$  product page.



## **CHV-RTHS**

## Remote Temperature and Humidity Sensor

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at <a href="https://www.crestron.com/How-To-Buy/Find-a-Representative">www.crestron.com/How-To-Buy/Find-a-Representative</a> or contact us for additional information by visiting <a href="https://www.crestron.com/contact/our-locations">www.crestron.com/contact/our-locations</a> for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

The product warranty can be found at www.crestron.com/warranty.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2024 Crestron Electronics, Inc.

Rev 02/05/24



# **CHV-RTHS**

# Remote Temperature and Humidity Sensor





