

# Comparison Guide

## Crestron MPC Media Presentation Controllers

| Feature Comparison                         | MPC-M10 | MPC-M20 | MPC-M25 | MPC-M5    | MPC-M50 |
|--|---------|---------|---------|-----------|---------|
| Number of programmable “hard key” buttons  | 10      | 15      | 15      | 10        | 7       |
| Illuminated LCD display with 4 “soft keys” |         |         |         |           | ●       |
| 5-way directional navigation pad           |         | ●       | ●       |           |         |
| Volume knob                                | ●       | ●       | ●       |           | ●       |
| LED bar graph                              | ●       | ●       | ●       |           |         |
| MPC Wizard setup                           | ●       | ●       | ●       | ●         |         |
| Fully customizable via programming         | ●       | ●       | ●       | ●         | ●       |
| Cresnet port                               | ●       | ●       | ●       |           | ●       |
| Number of bidirectional RS-232 COM port(s) | 1       | 1       | 2       | 1         | 2       |
| Number of IR/serial port(s)                | 1       | 1       | 2       | 1         | 2       |
| Number of relay control port(s)            | 2       | 2       | 6       | 2         | 6       |
| Number of input ports                      | 4       | 4       | 4       | 2         | 4       |
| Built-in 10/100 Ethernet                   | ●       | ●       | ●       | ●         | ●       |
| Built-in SNMP support                      | ●       | ●       | ●       | ●         | ●       |
| Built-in ambient light sensor              | ●       | ●       | ●       |           | ●       |
| SSL network protection                     | ●       | ●       | ●       | ●         | ●       |
| 2-gang wall mountable                      |         |         |         | ●         |         |
| 3-gang wall mountable                      | ●       | ●       | ●       |           | ●       |
| Includes external Cresnet power supply     | ●       | ●       | ●       |           | ●       |
| Power over Ethernet (PoE) network powered  |         |         |         | ●         |         |
| Built-in IR receiver                       | ●       | ●       | ●       | ●         | ●       |
| Real-time clock                            | ●       | ●       | ●       | Emulated* | ●       |
| RoomView® Express support                  | ●       | ●       | ●       | ●         | ●       |
| RoomView® Server Edition support           | ●       | ●       | ●       | ●         | ●       |
| TI DLP Support                             | ●       | ●       | ●       | ●         | ●       |
| Network-based software management          | ●       | ●       | ●       | ●         | ●       |
| Built-in Web server                        | ●       | ●       | ●       | ●         | ●       |
| XPanel UI support                          | ●       | ●       | ●       | ●         | ●       |
| FLASH                                      | ●       | ●       | ●       | ●         | ●       |
| Apple® iPhone®                             | ●       | ●       | ●       | ●         | ●       |

\* The internal time clock is reset after any reboot. If accurate time measurement is required, the MPC-M5 must be synchronized with an external time clock via the SIMPL™ Windows program.